



Description and features

Application

Physical constant

Tools

Storage

Health & Safety

Antique

Decorative paint, marbled , high-quality, gives marble effects, gives walls stylish touches of the finest overlapping colors with luxury gloss, characterized by good stability colors and gluing power, used for the final interior layers on concrete and cement and gypsum .

- 1 - All surfaces should be flat, clean and completely dry to be painted.
- 2 - Apply new coat with alzawaq insulator Almadina misurata.
- 3 - Apply two or three coats with "Almadina Misurata Putty " lengthwise and sideways, use sanding paper and then clean the dust
- 4 - Apply preparation coat of Al Madina Misurata "Latex Plus Matt".
- 5 - Apply two coats of Al Madina Misurata "Classic Matt" the same Antique color.
- 6 - Apply first coat of antique paint by putty knife toward irregular with constant change the angle of the tool and then leave it to dry for 45 minutes.
- 7 - Apply two coats in the same way with removal of all edges carefully.
- 8 - After (15-20 minutes) polishing the surface with using a piece of fabric or white gauze or putty knife.

Finish	Effect of marble
Color	By colors catalog
Specific gravity	1.5 ± 0.03 Kg/l
Viscosity	140 : 220 gr\cm ³
spreading rate	4 : 5 m / kilo
PH	8 : 9
Dilution	Ready for use without dilution
Dry to touch	15 : 20 minutes
Completely dry	1 : 2 hours.
Hardness	24 hours
Packing	1 kg , 3 kg



knife

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.