



دهانات المدينة مصراته

Almadina Misurata Paints | AMP®



Description and features

Application

Physical constant

Tools

Storage

Health & Safety

Epoxy «P.U205»

Paint epoxy "polyurethane", two compounds ,glossy, high-quality, interior and exterior, resistant to water influence , moisture and weather conditions and chemicals, Resistant to corrosion and friction and mechanical stresses, , made from the finest raw material in the world, used on concrete , cement and irons surfaces, And wooden surfaces.

For steel surfaces

- 1 - They are painted against rust paint is epoxy ZNP Almadina Misurata.
- 2 - They are painted PU 205 is paint the next day using a roller, spray gun, or brush.

For concrete surfaces

- 1 - A layer of epoxy 201 ciller is painted on concrete after glare.
- 2 - They are painted PU 205 is paint the next day using a roller, spray gun, or brush.

Color	White, gray, beige
Volume of solid	62%
Density "kg / l"	1.31 ± 0.02
Coverage	4m ² / kg ,average thickness of 100 μ
Mixing two compounds ratio	6 : 1
Operating time	4 hours
Dry to touch	2 hours
Completely dry	24 hours
Completely Hardening	7 days
Recoat time	12:24 hours
Minimum. Operating temperature	8 ° m
Thinner	Epoxy Thinner



Brush



Roller



Spray gun

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@almadinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

Twitter icon amppaints

Instagram icon amppaints

www.amp.ly