







Latex «Matt»

Description and features

High quality, interior and exterior acrylic paint, extra whiteness the ratio of whiteness is up to 97%, high coverage, excellent washable, designed to resistant weather conditions, composite of pure acrylic emulsion. easy to apply and gives a matt smooth surface, used to concrete, cement and gypsum surfaces.and coat wood surfaces.

Application

- 1- All surfaces should be flat, clean and completely dry to be painted.
- 2- Apply the new surfaces with "alzawq insulator".
- 3- Apply two or three coats with (Almadina Misurata Putty), "lengthwise and sideways", use sanding paper and then clean the dust
- 4- Apply one coat with "alzahy Almadina Misurata" as an under coat
- 5- Apply two coats of "latex Almadina misurata" after dilution with 10% water according to surface state and thickness of coat.

Physical constant

Finish Matt "Silky" Color white

Specific gravity 1.58 : 1.60 Kg/l Viscosity 115:120 Krebs

Solid by Volume 46 + 2spreading rate 6:8 m2/ kilo PH 9 ± 0.5

Dry to touch 1/2 hours and completely dry after 6 hours.

Flash Point Non flammable

Thinner

water by 15 % first, 10% second coat from total weight, depending on the thickness of paint Thinning

layer and the state of the surface to be coated.

Weight 20 kg

Tools



Brush

and keep it away from direct sunlight.



Roller

Product should be stored in the original package for 12 months from the production date, store it under normal conditions



Spray gun

Storage

Health & Safety

- 1 Don't keep food in the empty package.
- 2 Keep it away from the reach of children.
- 3 Avoid direct contact with eyes or skin, in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 This product is free of polluted materials to the environment.

Libya - Misurata - Industrial Zone - Alaswak

Sales:

amppaints

amppaints1

amppaints

www.amp.ly



