

دهانات المدبنه مصرانه Almadina Misurata Paints Awr





Latex Semi-Gloss

Description and features

Application

Physical constant

Tools

Storage

Health & Safety

1- All surfaces should be flat, clean and completely dry to be painted.

2- Apply the new surfaces with "Alzwaq Insulator"

3- Apply two or three coats with (Almadina Misurata Putty) "lengthwise and sideways", use sanding paper and then clean the dust.

Acrylic paint, exterior and interior, Semi-Gloss, high quality, clear whiteness, excellent hiding power

to 90%,maximum washability, designed to resistant all weather conditions, compound of pure acrylic

emulsion, easy to use and gives a silky smooth surface, available in white and used on wood, concrete

4- Coats preparation should be painting with Latex Matt or Matt alkyd paint

5- Apply two coats of Latex "Semi-Gloss" "Almadina Misurata according to the desired color.

finish Semi-Gloss "Silky"

White Color

cement and gypsum surfaces.

Specific gravity 1. 22 ±0.05 Kg/l Viscosity 105:110 Krebs

Solid by Volume 32 + 2

spreading rate 6:8 m2/ kilo

PH 9 ± 0.5

Dry to touch 1/2 hours and completely dry after 6 hours

Flash Point Non flammable

Thinner

Thinning water by 50% first coat, 35% second coat of total weight, depending on the

thickness of paint layer and the state of the surface to be coated.

Weight 12 kg

Brush



Roller



Spray gun

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 Don't keep food in the empty package.
- 2 Keep it away from the reach of children.
- 3 Avoid direct contact with eyes or skin, in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 This product is free of polluted materials to the environment.

Libya - Misurata - Industrial Zone - Alaswak

Marketing: 00218918000047 marketing@almadinamisurata.com

Sales: 00218912125435

amppaints1

amppaints



www.amp.ly

