







Alkyd Water Base «Matt»

Description and features

Application

Physical constant

Tools

Storage

Health & Safety

A New generation of paints (water base), it has the same specifications of Alkyd paints , composite from pure Acrylic, for interior and exterior surfaces, using for cement, concrete and gypsum surfaces, High quality, Silky smooth surfaces, Extra whiteness, Highly washable, Anti-Bacterial, High coverage

- 1 The surfaces should be flat, clean and completely dry.
- 2 Apply one coat for the new surfaces by (Alzawaq insulator)
- 3 Apply two or three coats of Almadina misurata putty with lengthwise and widthwise, sand it and clean the dust.
- 4 Apply one preparation coat of (latex plus matt Almadina misurata).
- 5 Apply two coats of (water Alkyd Almadina misurata) after dilution with 10% water according to surface state and thickness of coat .

Finish matt White Color

Specific gravity $0.05 \pm 1.2 \text{ kg/l}$ Viscosity 105:110 Krebs

Solid by volume 32 ± 2

Spreading rate 8-10 m 2 /kilo thickness of 50 microns

PH

Dry to touch 1/2 hours and completely dry after 6 hours.

Flash Point Non flammable Thinning Water by 10% Weight 3 kg - 7 kg



Brush



Roller

Product should be stored in the original package for 24 months from the production date, store it un-



Spray gun

der normal conditions and keep it away from direct sunlight.

- 1 Don't keep food in the empty package.
- 2 Keep it away from the reach of children.
- 3 Avoid direct contact with eyes or skin, in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice.
- 4 This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing: 00218918000047 marketing@almadinamisurata.com

Sales:

amppaints

amppaints1

amppaints



www.amp.ly

