







Economic Humidity Insulator

Description and features High Quality Acrylic Insulator Paint for Interior and Exterior surfaces, Prevent water permeability High resistance to weather conditions, Very Adhesive , Manufactured from the best raw materials in the world , Used to isolate building surfaces from inside and outside , Cement walls and Concrete walls.

Application

- 1 The surfaces should be Plane , Clean and Completely Dry
- 2 Paint longitudinally one layer from the Economic Humidity Insulator 10% diluted with water
- 3 Paint transversely one layer from Economic Humidity Insulator 10 % diluted with water

Physical constant Color White - Transparent

85:90 krebs Viscosity

PΗ 8 - 9

Specific gravity 1.17 ± 0.05 Kg/l

spreading rat 6 m²/ kg on putty layer

Thinner water Packaging 10 kg

Tools



Brush



Roller



Spray gun

Storage

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & **Safety**

- 1 Don't keep food in the empty package.
- 2 Keep it away from the reach of children.
- 3 Avoid direct contact with eyes or skin, in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 This product is free of polluted materials to the environment.

Libya - Misurata - Industrial Zone - Alaswak

Marketing: 00218918000047 marketing@almadinamisurata.com

Sales:

amppaints

www.amp.ly amppaints



