



دهانات المدينة مصراتة

Almadina Misurata Paints | AMP®



Description and features

Application

Physical constant

Tools

Storage

Health & Safety

Penetrating Sealer

acrylic isolation high resistance the rain water . humidity alkalinity and all climate . it has ability to fill pores inside the surface for all surfaces . it has ability to adhesion the different surfaces . non-yellowing It resistance affected surfaces humidity after painted so that apply directly your plaster before any applying paint : it has high gloss in case of using varnish resistance to abrasion in case of varnish for concrete flooring and bricks

Filed of using

For painting different building raw materials such on concrete plaster .bricks .gypsum surfaces and wood to protect from humidity painting finish products also using as varnish for exterior paints such on graphite . santex . silicate . protecting from rain and changing color

- 1- Clean surfaces of dust, oil and grease
- 2- Apply with brush, roller or spray gun
- 3- Paint one or more layers according to the surface state

Color	Transparent
Solids ratio	24%
Coat Drought	10min
Completely Dry	3 hours
Second Coating Paint Time	6 hours
Rate of use	7 m ² / ltr
Thinning	almadinam misurata lacquer thinner
Weight	16 kg



Spray gun



Roller



Brush

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@almadinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

www.amp.ly

Twitter icon amppaints

Instagram icon amppaints