



MATT ALKYD PAINT

Description and features

Premium quality alkyd paint, semi-gloss, characterized by high coverage and good yellowing resistance, based on special types of binders which gives special characteristics in terms of silky gloss and excellent leveling. Apply on concrete, cement, wood and steel fabrics. Comply with the Libyan standard specifications.

Advantages: High opacity - Excellent spreading rate - Bright whiteness - High yellowing resistance - easy to apply and good leveling.

Application

For cement surface:

- Surface must be free from any dust, dirt or grease.
- for surface preparation Use Al Zawaq insulator one coat then apply 2 coat form Al Madina Misurata putty.
- Apply 2 Coats from Matt Alkyd paint product as finish coat.

For Metal surface:

- Surface must be free from any dust, dirt or grease.
- for surface preparation Use Antirust Al Madina Misurata one coat.
- Apply 2 Coats from Matt Alkyd paint product as finish coat.

Physical constant

Spread rate:

10 : 12 m² / 1 Kg

Dilution:

Diluent: normal Thinner Al Madina Misurata

Dilution Percent: 10 - 15 % depend on application method.

Drying time:

Surface dry: 1 - 3 hr

Full Dry: 16 hr

Recoating Time: 16 hr

Tools



Brush



Roller



Spray gun

Storage

Product valid for 24 months in the well-sealed original can, away from direct sun light and in proper storage conditions.

Health & Safety

Food shouldn't be stored in the empty can, product should be kept out of reach of children, avoid contact with eye, in case it happened wash with water the follow the medical instructions. The product is free from environmental pollutants.

