



CLASSIC SEMI-GLOSS

Description and features

Premium quality water base paint designed from pure acrylic Emulsion which give outstanding properties in terms hiding, whiteness, leveling and weathering resistance. Suitable for interior and exterior applications on concrete, cement and gypsum walls for homes, schools, hotels, airport halls and hospitals..

Advantages: Exceptional hiding and leveling, excellent adhesion, very good washability, high weathering resistance and environmentally friend.

Application

- Surface must be free from any dust, dirt or grease.
- for surface preparation Use Al Zawaq insulator one coat then apply 2 coat form Acrylic putty.
- Apply one coat Latex plus matt as under coat layer.
- Apply 2 Coats from AlMadina Classic product as finish coat.

Physical constant

Spread rate : 10 : 12 m² / 1 Kg

Dilution: 15-20 % with water

Drying time: Surface dry: 30 – 60 Min (depends on gloss level).
Full Dry: 2-4 hr (depends on gloss level).
Recoating Time: 8 hrs.

Tools



Brush



Roller



Spray gun

Storage

Product valid for 24 months in the well-sealed original can, away from direct sun light and in proper storage conditions.

Health & Safety

Food shouldn't be stored in the empty can, product should be kept out of reach of children, avoid contact with eye, in case it happened wash with water the follow the medical instructions. The product is free from environmental pollutants.

