



دهانات المدينة مسرة
Almadina Misurata Paints | AMP®



Description and features

Application

Physical constant

Tools

Storage

Health & Safety

Spackling Putty «American»

Spackling putty , based on acrylic, does not contain Asbestos , high-quality, easy to use, gives a smooth surface, resistant to sunlight and external factors, made from the best raw material in the world, used to repair cracks and spacers between walls, used on surfaces concrete , cement and gypsum.

- 1 - All surfaces should be flat, clean and completely dry to be painted .
- 2 - Apply new coat with “Alzwaq insulator Almadina Misurata”.
- 3 - Fill cracks with “Al Madina Misurata Spackling Putty”.

Color	White
Specific gravity	0.34 kg/l
Viscosity	400 : 440 gm./cm ³
PH	8 : 9
Dry to touch	1/2 hours and completely dry after 24 hours.
Flash Point	Non Flammable
Thinning	Ready for use without dilution
Package	1 L



Putty knife

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@aladinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

www.amp.ly

Twitter icon amppaints

Instagram icon amppaints