



دهانات المدينة مصراتة

Almadina Misurata Paints | AMP®



Putty Al Madina Misurata “Interior”

Description and features

High quality interior acrylic putty easy to apply and offering excellent filling properties and hardness after dry , to be applied before using any kind of paints “emulsion paints” or “alkyd paint” to flatten the wall to become smooth and easy to paint .

Application

- 1 - The walls must be smooth clean and completely dry .
- 2 - first apply one coat from “Alzwaq insulator “ to fill the pores in the walls.
- 3 - Apply two or three coats from Almadina Misurata putty with lengthwise and widthwise then sand it and clean the dust .

Physical constant

Color	White
Specific gravity	1.71 ± 0.05 Kg/l
Viscosity	280: 360 Krebs
Solid by volume	52.9 ± 2
Spreading rate	2 m ² / kg first knife 8.5 ± 0.05
PH	1/2 hours and completely dry after 24 hours.
Dry to touch	Non Flammable
Flash Point	Water as needed
Thinner	1 kg - 4 kg - 10 kg - 18kg - 20 kg - 25 kg - 30 kg
Packaging	

Tools



Putty knife

Storage

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@almadinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

www.amp.ly

Twitter icon amppaints

Instagram icon amppaints