



## ALMADINA MISURATA PUTTY

### Description and features

High quality interior acrylic putty easy to apply and offering excellent filling properties and hardness after dry , to be applied before using any kind of paints "emulsion paints" or "alkyd paint" to flatten the wall to become smooth and easy to paint.

### Application

- The walls must be smooth clean and completely dry .
- First apply one coat from "Alzwaq insulator " to fill the pores in the walls.
- Apply two or three coats from Almadina Misurata putty with lengthwise and widthwise then sand it and clean the dust .

### Physical constant

<b>Color :</b>	White
<b>Specific gravity :</b>	1.71 ± 0.05 Kg / L
<b>Viscosity :</b>	280: 360 Krebs
<b>Solid by volume :</b>	52.9 ± 2
<b>Spreading rate :</b>	2 m <sup>2</sup> / kg first knife
<b>PH :</b>	8.5 ± 0.05
<b>Dry to touch :</b>	30 min. - completely dry : after 24 hours.
<b>Flash Point :</b>	Non Flammable
<b>Thinner :</b>	Water as needed
<b>Packaging :</b>	1 kg - 4 kg - 10 kg - 18kg - 20 kg - 25 kg - 30 kg

### Tools



Putty knife

### Storage

Product valid for 12 months in the well-sealed original can, away from direct sun light and in proper storage conditions.

### Health & Safety

Food shouldn't be stored in the empty can, product should be kept out of reach of children, avoid contact with eye, in case it happened wash with water the follow the medical instructions. The product is free from environmental pollutants.

