



دهانات المدينة مصراتة

Almadina Misurata Paints | AMP®



Chamoah

Description and features

Decorative paint, interior , high-quality, gives walls elegance and beauty with its applications of various decorative materials, characterized by good stability colors , gluing power and durability , made from the finest acrylic in the world, used for the final interior layers on concrete and cement and gypsum .

Application

- 1 - All surfaces should be flat, clean and completely dry to be painted.
- 2 - Apply one coat alzawaq insulator Almadina misurata.
- 3 - Apply two or three coats with "Almadina Misurata Putty" lengthwise and sideways", use sanding paper and then clean the dust .
- 4 - Apply preparation coat of Al Madina Misurata "Latex Plus Matt".
- 5 - Apply coat of Al Madina Misurata "Roshen", "Classic Matt" according to the desired decorative form.
- 6 - Apply coat or two of chamoah with using Roller , brush , sponge or printing tool .

Physical constant

Color	(Silver-gold) By colors catalog
Specific gravity	1.05 ± 0.03 Kg/l
Viscosity	135 :145 Krebs
spreading rate	10 : 12 m2/ kilo
PH	8 : 10
Dilution	Dilute according to the application
Dry to touch	15 : 20 minutes
Completely dry	4 hours
Hardness	24 hours
Packing	1 kg

Tools



knife



Roller



printing tool



sponge

Storage

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

amppaints1

amppaints

amppaints

amppaints

www.amp.ly