



دهانات المدينة مصراتة

Almadina Misurata Paints | AMP®



Description and features

Application

Physical constant

Tools

Storage

Health & Safety

Classic Matt

Exterior and interior matt Acrylic Paint, Extra whiteness , High coverage , Silky smooth surfaces , Highly washable , Resistant to weather conditions , using for all surfaces cement, concrete, and gypsum surfaces, It manufactured to correspond the Libyan standard specification No-455, Holds a Libyan quality mark.

- 1 - The surfaces should be flat, clean and completely dry.
- 2 - Apply one coat of (Al zawaq insulator).
- 3 - Apply two or three coats of (Almadina misurata putty) with lengthwise and widthwise, sand it and clean the dust.
- 4 - Apply one preparation coat of (latex plus matt Almadina misurata).
- 5 - Apply to coats of (classic matt) After dilution of 15% in the first coat according to surface state and thickness of coat .

finish	matt
Color	White and more than 8000 color according to Almadina Misurata computer coloring system
Specific gravity	1.30 ± 0.05 Kg/l
Viscosity	125 : 130 Krebs
Washability	it has high portability washing , it gives more than 2000 cycle on Wash ability test, That Specialized for measuring frictional resistance.
Solid by Volume	32 ± 2
Spreading rate	10 : 12 m2/ kilo Thickness of 50 microns,
PH	8.5 ± 0.5
Dry to touch	1/2 hours and completely dry after 24 hours.
Flash Point	Non flammable
Thinner	water
Thinning	water by 15 % for first coat and 10% second coat.
Packaging	5 kg - 15 kg



Brush



Roller



Spray gun

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

amppaints1

amppaints

amppaints

amppaints

www.amp.ly