



# دهانات المدينة مصراته

Almadina Misurata Paints | AMP®



## Epoxy 3D

### Description and features

Epoxy Varnish has high transparent and high shiny high friction and water resistant.

Are two component empty from solvent After its application give high shiny and transparent glass layer using above 3d floors image.

Only for internal using and can be using as adhesive for 3d floors image and also using as epoxy putty after adding calcium carbonate using as ceramic tiles breaks.

### Application

- 1 -The surface is strongly cleaned from Oil, grease, water and dust.
- 2 - They are stuffing the breaks by epoxy putty which made from same material after adding carbonate calcium
- 3- Emery the putty and ceramic and transform the shiny layer of ceramic by using emery grinder.
- 4- Make a layer of varnish by using roller under the 3d floor image and after dried The image is pasted by the same transparent epoxy material
- 5 - Take out the air well from below the image
- 6- Coverage the 3d epoxy on the 3d picture thickness 1.5mm by rate 1.5 kg per one meter by using plastic comb
- 7- Take out the air by using deflation roller especially for epoxy work

### Physical constant

Color	high transparent after covering
Composite weight	1.900 A KG
Composite weight	1.100 B KG
Operating period	after mixing the 2 composites 20minutes
Initial drying time	10 hours
Time of full sclerosis	6 days
Consumption rate	1.5 kg per one meter
Weight	3 kg
Using	internal

**Notes:**The kind of paper using for printing the picture has to be contain pores to let the epoxy interfere through and stick in the floor such as mesh papers or canvas papers , venal papers not recommended to use



Brush



Roller



Notched Trowel

### Tools

### Storage

The product is stored in his original package for 24 months from the production date. Under appropriate natural conditions The product should not be exposed to direct sunlight

### Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@almadinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

[www.amp.ly](http://www.amp.ly)

Twitter icon amppaints

Instagram icon amppaints