



دهانات المدينة مصراتة
Almadina Misurata Paints | AMP®



Mastic «Filler Cracks»

Description and features

Mastic putty, one compound based on acrylic emulsion, rubbery, interior and exterior, high-quality, resistant to sunlight and external factors, made from the best raw material in the world, used to repair cracks and spacers between walls, door frames and windows

Physical constant

Color	Rubbery Transparent
Specific gravity	1.2 ± 0.05 Kg/l
Viscosity	50 : 100 gm./km ³
spreading rate	According to the depth of the slit that needed to fix
Dry to touch	1 hour
Completely drying time	24 hours
Flash Point	Non Flammable
Thinning	Water , no more than 10%
Package	1 kg - 3 kg

Tools



Brush



Roller

Storage

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

amppaints1

amppaints

www.amp.ly

amppaints

amppaints