



Description and features

Application

Physical constant

Tools

Storage

Health & Safety

Matt Alkyd Paint

High Quality Exterior and Interior Matt Alkyd Paint, High coverage , Non - Yellowing, using for cement, concrete, wood and iron surfaces. Available in white and other colors.

concrete surface :

- 1 - The surfaces should be flat, clean and completely dry.
- 2 - Apply one coat of (Al zawaq insulator Almadina misurata) .
- 3 - Apply two or three coats of (Almadina misurata putty) with lengthwise and widthwise, sand it and clean the dust.
- 4 - Apply one or two coats of (Almadina misurata Matt Alkyd) After dilution about 10 - 15 % by mineral turpentine water one day should be allowed between the coats.

Iron Surfaces :

- 1 - The surfaces should be flat, clean and completely dry.
- 2 - Apply one coat for The new surfaces by (Almadina misurata Anti - rust primer)
- 3 - Apply one two coats of (Almadina misurata Matt Alkyd) After dilution about 10 - 15 % by mineral turpentine water one day should be allowed between the coats.

Color	White and colors
Specific gravity	1.2 ± 0.05 Kg/l
Viscosity	110 : 115 Krebs.
Spreading rate	10 : 12 m ² / 1L
Dry to touch	4 : 6 hours and completely dry after 24 hours.
Thinner	kerson
Packaging	4 kg



Brush



Roller



Spray gun

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.