



# دهانات المدينة مسurate

Almadina Misurata Paints | AMP®



## Description and features

## Application

## Physical constant

## Tools

## Storage

## Health & Safety

# SILICATE

Acrylic textured paint with quartz stonesand selected marble grains ,high-quality, interior and exterior, resist to all weather conditions, water-repellent, extreme gluing to surfaces, anti-friction, constant colors, gives a beautiful decorative forms, used to paint buildings from abroad, for decoration and weather protection .

1. All surfaces should be flat, clean and completely dry to be painted.
2. Apply the new surfaces with "AlZwaq Insulator"
3. Apply coat of Graphite "Almadina Misurata" according to required shape and decoration.

Color	White, Colors
Specific gravity	1.85 ± 0.05 kg / l
Viscosity	300: 390 g / cm
Coverage	7 : 8m <sup>2</sup> /18 kilo
PH	8 : 9
Flash Point	Non - Flammable
Thinner	Water when needed
Packaging	18 kg



Trowels

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@almadinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

Twitter icon amppaints

Instagram icon amppaints

[www.amp.ly](http://www.amp.ly)