



Alkyd Water «Satin»

Description and features

water base paint, it has the same specifications of Alkyd paints, composite from pure Acrylic for interior and exterior surfaces, using for cement, concrete and gypsum surfaces High quality, Silky smooth surfaces, Extra whiteness, Highly washable, Anti-Bacterial, High coverage

Application

- 1 - The surfaces should be flat, clean and completely dry.
- 2 - Apply one coat for the new surfaces by (Alzawaq insulator)
- 3 - Apply two or three coats of (Almadina misurata putty) with lengthwise and widthwise, sand it and clean the dust.
- 4 - Apply one preparation coat of (latex plus matt Almadina misurata).
- 5 - Apply two coats of (Water Alkyd Almadina misurata) after dilution with 10% water according to surface state and thickness of coat .

Physical constant

Finish	Satin
Color	White
Specific gravity	0.05 ± 1.2 kg/l
Viscosity	105 : 110 Krebs
Solid by volume	32 ± 2
Spreading rate	10:12 m ² /L thickness of 50 microns
PH	8 : 9
Dry to touch	1/2 hours and completely dry after 6 hours.
Flash Point	Non flammable
Thinning	By Water 10%
Weight	4 kg - 7 kg

Tools



Brush



Roller



Spray gun

Storage

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

