



دهانات المدينة مصراطة

Almadina Misurata Paints | AMP®



Wood Glue

Description and features

White glue for wood, high-quality, "based on polyvinyl acetate", high gluing power, very fast drying and give clear layer after drying also has high flexibility made from the finest materials in the world, used to glue natural wood, particleboard wood, Plywood, wood veneer and compacted wood boards, Available in white and transparent

Application

1. Surface must be dry, free of dirt, oil and grease to be painted.
2. Glue should be mixing well before using and apply it with brush or Rolla and spray gun.
3. To ensure gluing strength, glue should be waited from 5 to 15 minutes after gluing and before coating
4. Gluing Parts must be put under pressure between 2: 6 kg / cm² for 30:120 minutes.
5. Maximum gluing power obtained after 24 hours.

Physical constant

Color	White
Volume of Solid	54% (approximately)
Density (kg / l)	1.05 ± 0.01
Coverage	150: 300 g / m ² according to surfaces and used tools
Viscosity	30 ± 10 Boaz
PH	8 ± 0.5
Packing	1 kg , 3kg

Tools



Brush



Roller

Storage

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

amppaints1

amppaints

www.amp.ly

amppaints

amppaints