



دهانات المدينة مصراته

Almadina Misurata Paints | AMP®



Epoxy S.F 206

Description and features

Epoxy paint consisting of two boats, Free of solvent ,based on liquid epoxy resin and selected pigments, resistant to water influence , moisture and chemicals, Anti-Barre, friction and mechanical stresses, made from the finest raw material in the world, used for concrete , cement, irons surfaces, that And exposed to hard conditions such as chemical plants, spinning and weaving, workshops, distillation units, boilers, dairies, laundries, garages, nuclear power plants, warehouses, stairways, rooms and hospital operating rooms ,also for painting roads, bridges and sewage plants, paint tanks and iron pipes and machinery. And steel structures exposed to the influence of chemical agents or difficult conditions.

Application

- 1 - Surface must be dry, free of dirt, oil and grease to be painted.
- 2 - Apply coat or two of "Sealer Epoxy 201" or Epoxy Sealer according to porous surface after mixing the tow compounds well, mechanically mixing(at 300cycle/mi) using roll, brush and spray gun.
- 3 - Apply coat or two of Epoxy S.F 206 paint " Almadina Miusrata" according to porous surface after mixing the tow compounds well, mechanically mixing(at 300cycle/mi) the period between successive faceted 12 hours at 25 ° m .
- 4 - For anti-slip coat, spray on first coat or based coat clean sand (diameter 0.2: 0.7 mm at a rate of 1 kg / m²), then paint the final coat of Epoxy S.F 206 paint " Almadina Miusrata".

Physical constant

Color	White / colored
Solids by volume	100%
Density (kg / l)	1.22 ± 0.02 for Transparent & 1.36 ± 0.02 for colored
Mixing of the two compounds ratio	(A) 0.750 : 2.75 (B)
Operating time	30 minutes (less time to increase operating temperature)
Dry to touch	5:6 hours
Completely dry	24 hours
Completely Hardening	7 days
Recoat time	18:24 hours
Minimum. Operating temperature	8 ° m
Thinner	Do not dilute
consumption rate	306 g / m ² for each face 306 microns thick (colored)

Tools



Brush



Roller



Spray gun

Storage

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@almadinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

www.amp.ly

Twitter icon amppaints

Instagram icon amppaints