



دهانات المدينة مصراته

Almadina Misurata Paints | AMP®



Epoxy m.s.f 207

Description and features

Epoxy glossy colored paint self leveling, three compounds , solvent-free, based on liquid epoxy resin, Selected pigments, quartz , additions, hardener special amino, used for floors that exposed to chemicals impact and difficult conditions such as chemical factories Floors ,spinning and weaving plants, workshops and distillation units , boilers , laundries and dairy plants and for the massacres , garages, nuclear power plants, Stores, Stairs, hospitals rooms and , facilities , roads , bridges and sewage plants.

Application

- 1 - Surface must be dry, free of dirt, oil and grease to be painted.
- 2 - apply preparation coat of a Epoxy sealer 201 on concrete surfaces by roller.
- 3 - Compounds A, B, C should be mixed well with using slow speed mixer (300 cycle max).
- 4 - After thoroughly mixing components can be applied by Notched Trowel.
- 5 - The air is discharged by the special spherical roller using epoxy.

Physical constant

Color	grey / & another colors
solids	100%
Mixing of compounds ratio	A 8.800 kg – B 3.2 kg – C 10 kg
Operating period	20 minutes
Dry to touch	6:5 hours
Completely Drying	24 hours
Hardening	7 days
Recoat time	18 : 24
Minimum operating temperature	5 ° m

Tools



Notched Trowel

Storage

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

amppaints1

amppaints

www.amp.ly

amppaints

amppaints