



دهانات المدينة مسرة

Almadina Misurata Paints | AMP®



Description and features

Non - shrink epoxy adhesive putty good quality two components epoxy putty
For smoothing cement based plasters and concrete walls before application of epoxy paints
Repair edges and corners of staircases, beams and columns.
Filling and repairing cracks and voids in concretes

Application

The concrete or cement surface must be dry (dampness not more than 4%), firm, free of dust, laitance, oil, Grease and other impurities.

- It is preferable apply primer coat sealer epoxy 201

The two components of epoxy putty should be thoroughly mixed together using a slow speed mixer (Maximum 300 R.P.M).

• Apply the product by suitable steel putty knife.

Physical constant

Color	White / grey
Solid content	100 %
Mixing ratio	A:B 2 A : 1 B
Pot life	30 minutes
Initial setting time	2 hours
Final setting time	24 hours
Full hardness	7 day
Weight	4 Kilo
Recoating time	24 hours
Rate of use (theoretical)	250g / m2 (depending on surface conditions)
Packages	4 kg (A + B) A 2.700 – B 1.300 kg

Tools



Brush



Roller



Spray gun

Storage

The product is stored in his original package for 24 months from the production date. Under appropriate natural conditions The product should not be exposed to direct sunlight

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

facebook icon amppaints1

youtube icon amppaints

www.amp.ly

twitter icon amppaints

instagram icon amppaints