



دهانات المدينة مصراته

Almadina Misurata Paints | AMP®



Epoxy Sealer 201

Description and features

Epoxy paint, Preparatory, high quality, “consistent of two compound”, fills the pores and strengthens concrete surfaces, prepare surfaces to receive follows epoxy coats, made from the finest raw material in the world, used for concrete and cement surfaces.

Application

- 1 - Surface must be dry, free of dirt, oil and grease to be painted.
- 2 - Apply coat or two of “Epoxy Sealer” according to porous surface after mixing the tow compounds well, mechanically mixing(at 300 cycle/min.) using roll, brush and spray gun.

Physical constant

Color	Transparent
volume solids	40% ± 1%
specific gravity (kg / l)	0.9 ± 0.02
Two compounds mixing ratio:	1 : 5 wt.
Operating period	4 hours
Dry to touch	2 hours
Completely dry	7 days
Recoat time	12:24 hours
Minimum operating temperature	5 ° m
Coverage	4 : 5m ² / kg / face “according to the porosity of the surface”

Tools



Brush



Roller



Spray gun

Storage

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : 00218918000047 marketing@almadinamisurata.com

Sales : 00218912125435

amppaints1

amppaints

amppaints

amppaints

www.amp.ly