



## Description

## Wood Sealer Nitro

Nitrocellulose Sealer – High Viscosity, fast-drying, high-build sealer formulated with modified nitrocellulose, plasticizers, combined with selected resins and additives. It is designed to penetrate and fill wood pores effectively, providing a smooth, uniform surface ready for sanding and finishing with nitrocellulose or other compatible topcoats. Suitable to be applied on interior furniture, doors, MDF, prefinished in wood coating lines.

### Features :

- Excellent filling and pore-sealing properties.
- High build with fewer coats.
- Fast drying and easy to sand.
- Excellent intercoat adhesion.
- Smooth, uniform surface for subsequent topcoats
- Compatible with most NC /PU topcoats (Clear and Pigmented finishes).
- Substrate must be clean, dry, and free from oil, grease, dust, and previous incompatible coatings.
- Dilute with 150 – 200% with Acrylic thinner Al Madina Misurata.
- Apply with spray or brush one or two coats.
- Sanding with sandpaper 150 – 180 to make surface ready for topcoats

## Application method

## Drying Time

Surface dry: 10- 20 min  
Hard dry: 4-6 hrs  
Recoating intervals: 30 – 45 min

## Application tools



Spray gun

## Storage and validity

Product valid for 24 months in the well-sealed original can, away from direct sun light and in proper storage conditions.

## Health & Safety

Food shouldn't be stored in the empty can, product should be kept out of reach of children, avoid contact with eye, incase it happened wash with water the follow the medical instructions.

