



Description and features

Modified alkyd varnish polyurethane paint in one glossy compound, high-quality, interior and exterior, characterized by strongly gluing and high hardness, resistant to water and weather conditions, gives a smooth surface with high silkiness also shows the beauty of wood tanned, used to paint furniture, all interior and exterior woodwork and available in transparent color and colors catalog.

Application

1. All surfaces should be flat, clean and completely dry to be painted.
2. Apply preparation coat of "wood sealer" or many coats, to get to the required softness degree, then use sanding paper after each coat.
3. Apply one, two or more coats of "varnish wood PU" to get to the required point of color and smoothness .

Physical constant

Color	Transparent 8 color
Specific gravity	0.94 ± 0.05 kg / l
Viscosity	110 ± 5 krebs
Coverage	8 : 9 m ² /liter
Dry to touch	1 hours and completely dry after 24 hours
Thinner	A cold thinner or kerosene
Thinning	10 : 15%, depending on the thickness of paint layer and state of the surface
Packing	1 kg - 3 kg

Tools



Brush



Roller



Spray gun

Storage

Product should be stored in the original package for 12 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.