



Bond Crete

Description and features

A water-based coating formulated from flexible polymers and special aggregates that provide high hardness and roughness. It is used as a high-performance adhesion promoter, particularly suitable for smooth concrete surfaces (Fair Face), enhancing the bond with subsequent plastering layers. It is also effective on non-absorbent substrates such as ceramic, marble, granite, and porcelain, as well as absorbent surfaces including gypsum, concrete, cementitious, and wooden substrates, providing a textured finish that improves the adhesion strength of subsequent layers for both interior and exterior applications. The product is environmentally friendly and solvent-free.

Advantages:

- High adhesion strength - gives a rough surface and strong cohesive strength.
- Enhances adhesion to glossy and smooth surfaces.
- Highly flexible.
- High weathering resistance.

Application

- The surface to be painted must be completely free of dust and grease
- The product must be stirred well before use
- Apply One or two coats from the product, depending on the nature of the surface and the degree of roughness required, taking into consideration the recoating intervals.

Physical constant

Dilution:	5 -10 % with water
Drying time:	Surface dry: 40-60 Min Full Dry: 24 hrs
Recoating Time:	4 hrs
Spread Rate:	3 m ² /1kg

Tools



Brush



Roller



Spray gun

Storage

Product valid for 24 months in the well-sealed original can, away from direct sun light and in proper storage conditions.

Health & Safety

Food shouldn't be stored in the empty can, product should be kept out of reach of children, avoid contact with eye, in case it happened wash with water the follow the medical instructions.

